




# Reliable and robust

**KBK 25-System for festooned cable supply lines**


**DEMAG** .....

# Inexpensive and robust – easy to install for SWL up to 25 kg


A system for economic and reliable operation in handling installations and in mechanical engineering in general.



C-type track suspension arrangement



VR type suspension bracket (for square section tubing)



Track connecting clamp



Cable trolley with snap closure

## FEATURES OF THE DEMAG KBK 25 SYSTEMS:

- The light-weight robust components require minimum maintenance.
- High rigidity of the hollow section rail, low dead weight
- High resistance to wear
- Electro-galvanised for good resistance to corrosion
- Plastic or steel travel wheels mounted on anti-friction bearings which are lubricated for life
- Trolleys protected from corrosion by acid vapours
- Mass production of components ensures uniform quality
- Simple bolted connections enable do-it-yourself assembly
- Suspension arrangements suitable for all types of superstructure
- Flexibility of track layout

The Demag KBK 25 system may also be used for building light-duty cranes or monorails for easy movement of electric or pneumatic portable tools suspended by means of balancing devices, e. g. above assembly lines where drills, impact wrenches or soldering tools must be handled safely and efficiently.

In photographic and film studios the KBK 25 system with its smooth travelling trolleys is ideal for overhead suspension and movement of spotlights and microphones.

The trolleys are designed for loads of up to 25 kg and run smoothly and quietly in the hollow-section rail where they are protected from dirt and dust.

### Technical Data

Straight sections	5 m
Curved section	90°, R = 750, 1000, 1500 mm
Rail section dimensions	Height 40 mm, width 28 mm
Travel speeds	Up to 63 m/min
SWL	Max. 3, 15 or 25 kg/trolley
Temperature range	-20°C to +70°C

## DEMAG CRANES & COMPONENTS GMBH

Wetter site  
Ruhrstrasse 28  
58300 Wetter/Germany  
E info@demagcranes.com  
P +49 2335 92-0  
F +49 2335 92-7676  
www.demagcranes.com

# DEMAG